

Hydraulic Hand Stacker

Hydraulic Hand Stacker features a compact design, making it suitable for use in tight spaces and standard doorways. The stacker operates with both foot and hand controls, ensuring precise and smooth lifting. Its sturdy steel construction and heavy-duty twin chains provide excellent load stability. The stacker is engineered for easy maneuverability, allowing operators to navigate through congested areas effortlessly.

- Hand stacker provides cost effective handling for both vehicle loading and production areas.
- Sturdy and compact enough to fit through standard door and to operate in congested areas.
- Compact design.



Technical Parameters

Product Code	LEHS	1016	1030	1516	1525	2016
Capacity	kg	1000	1000	1500	1500	2000
Load Centrer	mm	400	400	400	400	400
Type of Lifting	Manual/ Foot	Manual/Foot	Manual/Foot	Manual/Foot	Manual/Foot	Manual/Foot
Wheel Type	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon
Minimum Fork Length	mm	85	85	85	85	85
Maximum Fork Height	mm	1600	3000	1600	2500	1600
Fork Length	mm	1150	1150	1150	1150	1150
Single Fork Size	mm	150	150	150	150	150
Overall Height	mm	2030	2080	2030	1800	2080
Minimum Turning Radius	mm	1520	1520	1520	1520	1520
Approximate Weight	kg	220	345	230	330	270